

What is claimed is:

- Sub. A15
- 5
- 10
- 15
- 20
- 25
- 30
- 35
- add A4
1. A method for removing a vapor-phase contaminant from a contaminated gas stream in a duct, said method comprising:
- adsorbing fresh sorbent onto the surface of a sorbent structure positioned inside said duct;
 - passing said contaminated gas stream over said fresh sorbent structure so that said vapor-phase contaminant is adsorbed by said fresh sorbent until saturated sorbent is produced;
 - periodically removing said saturated sorbent from said sorbent structure and collecting said saturated sorbent outside of said duct; and
 - repeating said adsorbing step with a new quantity of fresh sorbent.
2. The method of Claim 1 wherein said adsorbing additionally comprises:
- injecting said fresh sorbent into said contaminated gas stream prior to said passing.
3. The method of Claim 1 wherein said adsorbing is carried out prior to placing said sorbent structure inside said duct.
4. The method of Claim 1 wherein said vapor-phase contaminant comprises at least one substance containing mercury.
5. An apparatus for removing a vapor-phase contaminant from a contaminated gas stream in a duct, said apparatus comprising:
- at least one sorbent structure;
 - a means for adsorbing fresh sorbent onto said sorbent structure;
 - a means for passing said contaminated gas over said sorbent structure to produce saturated sorbent; and
 - a means for removing and collecting said saturated sorbent.